

CO₂ Mini Booster * carbo-Line

 Länge: 1300 Breite: 800 Höhe: 2000 Gewicht: max.900 kg	Kälteleistung TK Cooling capacity LT	Kälteleistung NK Cooling capacity MT	Gaskühler Leistung Gas cooler capacity	Max. Betriebsstrom Max operating current	Inhalt Sammler Receiver
	kw	kw	kW	A	l
carbo-Line BXH2-007 + 2NSL	2,5	12,1	23,1	25,1	60
carbo-Line BXH2-009 + 2NSL	2,5	14,9	28,1	32,7	60
carbo-Line BXH2-010 + 2NSL	2,5	19,0	33,6	34,3	60
carbo-Line BXH2-013 + 2NSL	2,5	25,8	44,6	45,9	60
carbo-Line BXH2-019 + 2NSL	2,5	39,6	65,0	46,9	60
carbo-Line BXH2-007 + 2MSL	3,3	11,2	23,1	25,5	60
carbo-Line BXH2-009 + 2MSL	3,3	14,0	28,1	33,1	60
carbo-Line BXH2-010 + 2MSL	3,3	18,1	33,6	34,7	60
carbo-Line BXH2-013 + 2MSL	3,3	25,0	44,6	46,3	60
carbo-Line BXH2-019 + 2MSL	3,3	38,8	65,0	47,3	60
carbo-Line BXH2-007 + 2KSL	5,5	8,5	23,1	26,5	60
carbo-Line BXH2-009 + 2KSL	5,5	11,4	28,1	34,1	60
carbo-Line BXH2-010 + 2KSL	5,5	15,4	33,6	35,7	60
carbo-Line BXH2-013 + 2KSL	5,5	22,3	44,6	47,3	60
carbo-Line BXH2-019 + 2KSL	5,5	36,1	65,0	48,3	60
carbo-Line BXH2-007 + 2JSL	7,1	6,6	23,1	27,6	60
carbo-Line BXH2-009 + 2JSL	7,1	9,4	28,1	35,2	60
carbo-Line BXH2-010 + 2JSL	7,1	13,5	33,6	36,8	60
carbo-Line BXH2-013 + 2JSL	7,1	20,4	44,6	48,4	60
carbo-Line BXH2-019 + 2JSL	7,1	34,2	65,0	49,4	60

Kältemittel: R744

Tiefkühlung bei -30/-5°C | 1 Verdichter 50Hz

Normalkühlung bei -5/36°C GK, Flashgasbypass | 2 Verdichter 50 Hz

